

Kenworth of Richfield 2890 Brecksville Rd Richfield, OH 44286 Ph: 330-659-4123 Fax: 330-659-4481 Toll Free: 800-362-7490

Stock Plow Truck Russell Township Sourcewell Member Number 42393

We are pleased to quote you on your New 2019 T370 Snow Plow Purchase. Please see attached specifications for your review and consideration.

Sale price for the 2019 Kenworth T370 White

Sourcewell/NJPA Contract #081716-KTC Per attached specs.

New 2019 KW T370 Chassis	\$84,198.00
Henderson Snow Package per specs	\$57,198.00
Title fees	<u>250.00</u>
Payment Due at Delivery	\$141,550.00

5 year 100,000 mile Engine and Engine After treatment Warranty ADD \$2,290.00

Payment Due at Delivery

Please call me on my cell with any questions

Thanks,
Ray Gindlesperger
Kenworth of Richfield and Canton
330-523-6493 cell#
330-659-4123
rgindlesperger@hissongkw.com





Kenworth of Richfield H200 2890 Brecksville Rd

Z STK - T370 4X2 MUNI PLOW

Richfield,	Ohio	United	States	44286
------------	------	--------	--------	-------

Phone: Phone: Fax: Fax:

Email: Contact Email:

Prepared for: Default Contact

Vehicle Summary

Unit	Chassis	
Model: T370 SERIES CONVENTIONAL	Fr Axle Load (lbs):	16000
Type: FULL TRUCK Description: 2019 Stock truck Application	Rr Axle Load (lbs) G.C.W. (lbs): Road Conditions:	23000 39000
Intended Serv.: Snowplow. Vehicles which are configured for	Class A (Highway)	85
Commodity: Other minerals	Class B (Hwy/Mtn) Class C (Off-Hwy)	10 05
Type: End dump Length (ft): 10.0 Height (ft): 12.0 Max Laden Weight (lbs): 4000	Class D (Off-Road) Maximum Grade: Wheelbase (in): Overhang (in): Fr Axle to BOC (in): Cab to Axle (in):	00 6 153 50 68 85
Trailer	Cab to Axie (iii). Cab to EOF (in):	135
No. of Trailer Axles: 0	Overall Comb. Length (in):	244
Type: 0.0 Length (ft): 0.0 Height (ft): 0.0 Kingpin Inset (in): 0 Corner Radius (in): 0	Special Req. U.S. Domestic Registry, 50-State	
Restrictions		
Length (ft): 120 Width (in): 102 Height (ft): 13.5		
Approved by:	Date:	

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:12/6/2018 10:39:10 AMCompleteModel Number:T370 SERIES CONVENTIONALEffective Date:Jan 1, 2018Quote/DTPO/CO:Q42420495Prepared by:AdministratorVersion Number:41.20

56337-DC11-0290 Page 1 of 9



Kenworth of Richfield H200 2890 Brecksville Rd

Z STK - T370 4X2 MUNI PLOW

Richfield, Ohio United States 44286 Phone: Phone: Fax: Fax: Contact Email: Email: Prepared for: Default Contact Description Weight Code Model 9.642 0000370 O **T370 SERIES CONVENTIONAL** Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark State Gray seat color; Floormat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 0070006 O T370 Class 7: medium-duty Conventional. CARB Idle Emissions Reduction Feature for PX-7 0080050 O Medium-duty 4x2 automatic. 0090015 O 0091240 O Other minerals Snowplow. Vehicles which are configured for 0093025 O mounting a snowplow to the front. May also have dump or other body. Typically includes some operation off of paved roads. Road usage: majority of Class A & B, do not code for Class D. 0095010 O End dump 0098025 O U.S. Domestic Registry, 50-State 0 **Engine & Equipment** 555 0129552 O PACCAR PX-9 350 2017 350@2000 340@2100 1000@1400 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09200 N205 120. Standard Maximum Speed Limit [LSL] N09220 N207 0....Expiration Distance N09260 P14 66...Maximum Accelerator Pedal Vehicle Speed N09300 P19 66...Maximum Cruise Speed N09360 N203 252..Reserve Speed Function Reset Distance N09380 N202 0....Maximum Cycle Distance N09400 N206 10...Maximum Active Distance N09420 N201 0....Reserve Speed Limit Offset N09440 P11 NO...Engine Protection Shutdown N09460 P06 NO...Gear Down Protection N09480 P26 1400.Max PTO Speed N09500 P02 NO...Cruise Control Auto Resume N09520 P04 NO...Auto Engine Brake in Cruise

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 2 of 9



Data	Code	Description N09540 N209 0Expiration Distance N09560 P520 YESEnable Idle Shutdown Park Brake Set N09580 P32 5Timer Setting N09600 P233 YESEnable Impending Shutdown Warning N09620 P234 60Timer For Impending Shutdown Warning N09640 P516 35Engine Load Threshold N09680 P33 NOIdle Shutdown Manual Overrule N09720 P230 YESEnable Hot Ambient Automatic Overrule N09740 P46 40Low Ambient Temperature Threshold N09780 P56 60Intermediate Ambient Temperature Threshold N09780 P47 80High Ambient Temperature Threshold	Weight
1000063	U	APPL APPROVAL RQD-CLASS C/D ROAD USE	0
1000156	0	Prospector Version 42.0	0
1000684	0	Replaces 41.2 Effective VSL Setting NA	0
1000858	0		
1000859	0	Engine Idle Shutdown Timer Disabled Enable EIST Ambient Temp Overrule	0
1000891	O	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	Ò
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	0
1099301	0	Pre-filter hood mounted for air cleaner & HVAC.	13
1105230	Ö	Fan Hub: Horton 2-Speed for ISL9, ISL-G, PX-8 or PX-9	0
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0
1247194	0	Exhaust:2017 EPA RH Under Cab DPF/SCR For PX-9 w/ Single Vertical RH Side of Cab Tailpipe.	215
1290124	0	Single Vertical RH Side of Cab Tailpipe. Tailpipe: 5 in. single 24 in. 45 degree curved.	-2
1321145	0	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	0
1321200	0	Run Aid:None *For Fuel Filter	O
1321305	0	Start Aid:12V Heat *For Fuel Filter	1
1504006	0	Block heater, PACCAR 1750 watt 120V for PX-6 and PX-7, 1000 watt for PX-8 and PX-9 or ISL9 engines .	2
1816160	0	Alternator: 160 amp brush type T3	0
1821210	0	Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	57

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 3 of 9



Data	Code	Description	Weight
1836100	S	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
1900082	0	Multi-function engine connector for body builder interface for Cummins.	0
Transmissi	ion & Clu		
2011205	0	Transmission: Allison 3000RDS 6-speed w/PTO drive gear. 5th Gen controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models.	291
2401405	0	Driveline: 2 Dana standard-duty; 1 centerbearing. *Standard duty is 1710 series.	77
2409916	0	One bolted centerbearing crossmember. This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	11
2410018	0	Torque converter included w/Allison Transmission.	Ò
2410204	0		
2429358	0	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
Crest Avle	P. Envisor	namé	
2504160		Dana Spicer D1600 Front Axle 16K standard track.	120
2603006	S	Front brakes included w/ front hub package.	0
2659047	0	Front dustshield: for drum brakes: all front axles.	6
2703016	Ó	Front Brake:Bendix 16.5x6 air brake package for 16K non-driving front axle. Includes cast drums, iron 10-bolt hub pilot Preset hubs, hub caps, oil seals & slack adjusters. For use with 22.5 inch wheels	75
2864026	0	Front Springs Taperleaf 16K 2-stage with shocks and 54 in. spring length. T370 w/16K front axle.	172
2895300	Ö	Dual power steering gears: 16K.	77
2899336	0	Power Steering Cooler:Radiator Mounted Air-to-Oil	11

Rear Axie & Equipment

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018	•	Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number	41.20

56337-DC11-0290 Page 4 of 9



Data	Code	Description	Weight
3041190	0	Single Dana Spicer S23-190 single reduction rear axle. Single rear axle rated at 23K.	255
3200614	0	Rear Axle Ratio - 6.14.	0
3300000	S	Single rear brakes included w/rear hub package.	0
3401001	S	23K air brake package includes 16-1/2x7 in. brakes, cast drums, aluminum 10-bolt hub pilot Preset hubs, automatic slack adjusters and oil seals for use w/ 22.5 in. wheels.	0
3485009	S	Spring Brake: 3030 high output single.	0
3490047	0	Spring Brake: 3030 high output single. Dustshields for drum brakes: all rear axles.	11
3495226	S		
3531001	0	Wheel Differential Lock for Dana Spicer Axles S21-170, S21-190, S23-170, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	28
3636422	0	Rear suspension: single Reyco 79KB taperleaf 23K. Medium-duty. Unladen Height: 9 in. Laden Height: 7.3 in. Not rear air disc	57
3836315	0	Bolted rear suspension crossmembers for Reyco 79KB. Replaces T3 standard.	41
Tires & Wh	eels		
4038677		Front tires: Goodyear G291 315/80R22.5 18PR. 42.3 in. diameter, all position. 19.7 in. SLR.	154
4238682		Rear tires: Goodyear G182 RSD 11R22.5 16PR. 42.1 in. diameter, all position. 19.6 in. SLR. Code is priced per pair of tires.	64
4900004	_	Rear Tire Quantity: 4	0
5045280	U	Front Wheel: Alcoa 89U64 22.5X9 AL Ultra ONE Wheel.	-24
5245162	0	Rear Wheel: Alcoa 88367 22.5x8.25 aluminum with Level One [TM] finish, hub-pilot mount. 7400 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels.	-88
5859010	0	Single Front Axle: 2 wheels Dura-Bright Buffed.	0
5859011	0	Dura-Bright outboard surface of aluminum wheels. Single Rear Axle Wheels: 2 wheels Dura-Bright Buffed. Dura-Bright outboard surface of outer dual or single aluminum wheels.	0
5900004	0	Rear Wheel/Rim Quantity: 4	0
Frame & Eq 6056200		Frame Ralls: 10-3/4 x 3-1/2 x 3/8in. Steel to 284 in. Truck frame weight is 3.48 lbin. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	145

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 5 of 9



Data 6308710	Code S	Description Bumper: Aerodynamic, Painted. Requires a	Weight 0
		bumper setting code.	
6319409	S	40.9 in. Bumper setting. Requires a bumper code.	0
6321005	0	Removable Front Tow Hooks: 2.	15
6390103	S	Front mudflaps.	0
6400636	0	Battery box cantilever aluminum BOC w/ fiberglass cover.	0
6409901	0	Battery box location: LH Side.	0
6451059	0	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under. End plates will be painted standard black frame color.	0
6490124	Ö	Five-plece bolted crossmember assembly with 16mm frame fasteners, center and rear frame.	-32
6490427	0	Aluminum underbell crossmember. Only with non-drive front axle 16K and greater. For T370 only.	19
6490430	0	Bolted Rear Cab Support Crossmember. Replaces T3 standard.	17
6721102	0	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	12
6722000	0	straight. Includes B1732 mounting brackets as standard. Rear mudflap shields: White plastic antisail w/ Kenworth logo.	9
6741023	Ö	Square end-of-frame w/ boited crossmember, non-towing.	41
Fuel Tanks	9. Equip		
7210056		Fuel Tank: 56 US gallon 24.5in. aluminum under replace.	-45
7722011	Ö	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	Ö
7889061	0	Polished stainless steel tank straps for 1 tank.	0
7889098	0	Polished straps for 1 DEF Tank any size.	0
7889203	0	Standard DEF to fuel fill ratio: 2:1 or greater.	0
7889604	0	DEF tank location is on the LH.	0
7920056	0	Location: 56 gal fuel tank LH under cab	0

Cab & Equipment

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 6 of 9



Data 8024310	Code S	Description Cab: Curved Glass Conventional.	Weight
0024310	3	Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
8090310	S	Hood: Sloped aerodynamic hood includes grill & separate bumper.	0
8108010	S	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
8201200	0	Adjustable telescoping tilt steering column.	10
8202996	Ö	Manual override switch: For fan hub, w/o warning lamp. For fire truck pumpers only. Option used to request fan on only. The engine may turn fan on and off on regardless of switch.	1
8208496	0	Three spare switches: Wired to power.	0
8220106	Ö	Gauge: Dash mounted air filter restriction gauge.	0
8282004		KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
8282009	S	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	Ò
8330003	S	Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	0
8410191	Ö	Driver seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	2
8480190	0	Rider seat: Kenworth Toolbox Plus HB vinyl. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted with a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	2
8496559	0	Driver and Rider Seat Belts: Orange Seat Belts. Replacing standard color.	0

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 7 of 9



Data 8601421	Code	Description Kenworth Radio with AM/FM/WB/USB and Bluetooth	Weight
	_		4
8700083	0	Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet & a storage compartment.	0
8700154	0	Self cancelling turn signal: W/head light dimmer switch.	0
8800200	S	Cab access contoured grabhandles, LH/RH.	0
8800400	0	Grabhandle: LH inside door frame above dash.	Ó
8800401	0	Grabhandle: RH inside door frame above dash.	2
8832115	0	Daylite Door: LH/RH includes RH peeper window	0
8841411	0	Single air horn under cab	3
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	0
8865000	O	Mirror: Dual Kenworth aerodynamic heated motorized 7 in. x 13 in. mirrors. Mirror shell painted cab color, mirror arms black. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8-1/2 ft load width. Switch located on door pad.	26
8871438	S	Rear Cab Stationary Window 17 in. x 36 in.	0
8879213	0	Electric-powered LH & RH door window lifts. Switch located on door.	0
Lights & Ins	strument	s	
9010801		Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
9022137	0	Marker Lights: Five, rectangular, LED	0
9030010	S	Turn Signal Lights: Mounted on fender	0
9070138	Š	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
9090845	Ö	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipm	ent		
9101215		Air Dryer Bendix AD-IS heated Puraguard	0
9140326	0	Additional 7-way electrical receptacle mounted end-of-frame.	2
Extended W	/arranty		
9200008		Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200022	S	Base Warranty - Standard Service Medium Duty 12 months / Unlimited miles & km	0

Printed:	12/6/2018 10:39:10 AM	Complete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q42420495
Prepared by:	Administrator		Version Number:	41.20

56337-DC11-0290 Page 8 of 9



Data	Code	Description	Weight
Miscellaneous 9400072 O		Ship to Dealer.	0
9409852	0	GHG Secondary Manufacturer: Does Not Apply	0
	U		U
9490003	0	Additional lead time required for off highway & /or specialty component truck.	0
Paint			
9700000	0	Paint color number(s).	0
		N97020 A - L0006 WHITE	
		N97200 FRAME N0001 BLACK N97700 BUMPER L0006 WHITE	
9943001	0	Bumper Painted Color A	0
9943050	0	Day Cab Standard Paint	Ó
9944820	O	1 - Color Paint - Day Cab	0
		Color will be White if no other color is specified.	
9960009	0	Fleet Paint – Dealer ECO Required	0
9965510	S	Base coat/clear coat.	0
		The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	
Total \Meigh			12054 IL
Total Weigh	L		12054 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:12/6/2018 10:39:10 AMCompleteModel Number:T370 SERIES CONVENTIONALEffective Date:Jan 1, 2018Quote/DTPO/CO:Q42420495Prepared by:AdministratorVersion Number:41.20

56337-DC11-0290 Page 9 of 9



RICHFIELD KENWORTH ATTN: RAY GINDLESPERGER

SINGLE AXLE HENDERSON SNOW AND ICE CONTROL EQUIPMENT STANDARD DUMP PACKAGE

4-10-2018

2 YEAR FULL WARRANTY ON ALL EQUIPMENT

*2 YEAR FULL WARRANTY ON ALL EQUIPMENT ONLY AVAILABLE WHEN A HENDERSON FACTORY OWNED UPFIT FACILITY DOES THE INITIAL INSTALLATION AND UP-FIT ON THE ENTIRE BUILD AND SERVICE AND WARRANTY WORK THERE AFTER.

*ALL MOUNTING 100% TO RICHFIELD KENWORTH SPECIFICATIONS

*PREDELIVERY INSPECTION AT OUR FACILITY PRIOR TO PAINT

*WARRANTY WORK AND SERVICE WORK- HENDERSON PRODUCTS-OHIO WILL PICK UP
THE VEHICLE AT YOUR LOCATION AND MAKE NECESSARY REPAIRS AND RETURN TO
YOUR FACILITY.

*ALL EQUIPMENT AND YOUR CHASSIS ARE FULLY INSURED WHILE IN HENDERSON PRODUCTS-OHIO POSSESSION.

TOTAL INSTALLED PRICE

\$57,102.00 EACH

<u>LEAD TIME:</u> FIRST 2 TRUCKS WILL PUT INTO THE AUGUST 2018 BUILD SCHEDULE, THE SECOND 2 IN SEPTEMBER 2018, THIRD 2 IN OCTOBER 2018, FOURTH 2 IN NOVEMBER 2018, FIFTH 2 IN DECEMBER 2018.

HENDERSON PRODUCTS-OHIO

DAN PERRY-OHIO SALES REP. CELL (440)-226-4690 FAX (563)-927-7161 DPERRY@HENDERSONPRODUCTS.COM

CONTRACT ACCEPTANCE:	DATE:	
PURCHASE ORDER #:	QUANTITY	











SEE ATTACHED SPECIFICATIONS:

HENDERSON DUMP BODY

- HENDERSON MODEL MARK E 10' STAINLESS STEEL DUMP BODY
- CROSSMEMBERLESS-UNIBODY DESIGN
- 201 STAINLESS STEEL CONSTRUCTION
- SLOPED LOWER DIRT SHEDDING RUB RAIL.
- 10' LONG
- 7' INSIDE WIDTH
- 30" TALL SIDES
- 38 " AIR TAILGATE WITH LIFT HOOK (D-RING)
- DOUBLE WELD-ON HORIZONTAL BRACES ON TAILGATE
- 1/4" AR400 STEEL FLOOR
- 5" SIDE TO FLOOR RADIOUS
- SLOPED BOX TOP RAIL
- SINGLE WELD-ON HORIZONTAL SIDE BRACES
- 8" REAR APRON
- FULL DEPTH REAR CORNER POST
- ONE PIECE FRONT CORNER POST
- 22" X 86" FULLY WELDED CAB SHIELD
- GRIP STRUT WALK RAILS ALONG BOTH SIDES OF BODY
- HENDERSON STAINLESS STEEL TUCK AWAY SIDE LADDER
- ALL LED FMVSS # 108 MARKER LIGHTS
- INSTALLED

HENDERSON HOIST

- HENDERSON MODEL CS FRONT TELESCOPIC MAILHOT HOIST
- 29 TON CAPACITY
- 12" FRONT INTERNAL DOGHOUSE
- 9" MOUNTING HEIGHT
- FULL DOUBLE ACTING HOIST
- GREASEABLE REAR STAINLESS STEEL PINS
- INSTALLED

HENDERSON PIN & LOOP SNOW PLOW HITCH

- HENDERSON PIN & LOOP LOW PROFILE FRONT FRAME SNOW PLOW HITCH
- HENDERSON MODEL 2-1/2" DROP PIN QUICK HITCH
- HENDERSON FULL 5/8" STEEL SIDE PLATES
- OEM BUMPERS
- 5 POSITION TELESCOPING LIFT ARM
- 4" DOUBLE ACTING LIFT CYLINDER
- PAINTED AND INSTALLED
- KENWORTH FRONT GRILL MODIFIED TO ACCOMMODATE THE PLOW HITCH

HENDERSON TGS-6 UNDER TAILGATE SPREADER

- HENDERSON MODEL TGS STAINLESS STEEL SPREADER
- 6" AUGER WITH 5:1 GEARCASE HYDRAULIC MOTOR

- ◎ ¼" END PLATES
- ¼" IN DROP PORT
- EASY EMPTY CLEAN OUT PAN
- STAINLESS STEEL TAILGATE FINS
- 18" POLY SPINNER DISC
- ALL STAINLESS STEEL MOUNTING HARDWARE
- INSTALLED

ELECTRICAL SYSTEM

- WHELEN LED LIGHT SYSTEM
- LED OBLONG AMBER STROBES RUBBER GROMMET MOUNTED IN THE CABSHIELD IN SEALED STAINLESS STEEL BOXES FACING FORWARD, SIDES AND TO THE REAR
- LED AMBER STROBE LIGHTS RUBBER GROMMET MOUNTED IN REAR CORNER POST
- LED BACK UP LIGHTS RUBBER GROMMET MOUNTED IN REAR CORNER POST
- LED STOP/TAIL/TURN RUBBER GROMMET MOUNTED IN REAR CORNER POST
- 4" LED SPINNER LIGHT
- MODEL SK-10 BODY UP LIGHT IN THE CAB
- WHELEN BACK UP ALARM
- ALL ONE PIECE WIRING FROM POWER SOURCE TO ELECTICAL ITEM
- ALL WIRING WILL BE PROPERLY RAN TO AVOID SHARP EDGES AND PINCH POINTS
- ALL WIRING WILL BE PROPERLY FUSED
- FACTORY REAR CHASSIS LIGHTS TO BE REINSTALLED
- HENDERSON PDP POWER DISTRIBUTION CENTER
- ALL LED FMVSS # 108 MARKER LIGHTS
- HEATED LED SNOW PLOW LIGHTS WITH STAINLESS STEEL BRACKETS
- ALL ONE PIECE WIRING WITH COPY OF WIRING SCHEMATIC

CERTIFIED POWER CENTRAL HYDRAULIC SYSTEM

- CERTIFIELD POWER-STORMGUARD/LOAD SENSING SYSTEM
- DANFOSS TRANSMISSION MOUNTED PUMP
- CHELSEA MODEL 890 WET SPLINE EXTENDED SHAFT PTO
- DANFOSS MODEL PVG CONTROL VALVE
- ELECTRIC CONTROL VALVE TO RUN BODY/SNOW PLOW/SPREADER
- STORMGUARD CUSTOM CONSOLE WITH ARM REST
- ELECTRIC JOY STICKS
- CERTIFIED POWER PLOW BALANCE SYSTEM
- HENDERSON STEEL FLOOR PLATE
- CERTIFIED POWER FREEDOM 2 SPREADER CONTROL SYSTEM
- HENDERSON 30-GALLON STAINLESS STEEL OIL RESERVOIR/VALVE ENCLOSURE
- ALL WEATHERHEAD HOSES AND FITTING WITH STAINLESS STEEL QUICK COUPLERS
- ALL PRESSURE HOSES SAE 100R2
- ALL FITTING JIC STYLE
- MID-STATE STAINLESS STEEL REAR HYDRAULIC TUBES FOR SPREADER
- MID-STATE STAINLESS STEEL FRONT HYDRAULIC TUBES FOR PLOW
- ALL SWITCHES MOUNTED IN STAND

- 6 HYDRAULIC SYSTEM WILL BE PROPERLY TESTED AND CALIBRATED
- INSTALLED

MISCELLANEOUS

- CHROME EXHAUST ELBOW
- WOOD SIDE BOARDS PAINTED COLOR OF CHOICE
- STAINLESS STEEL SHOVEL HOLDER
- 3/4" PINTLE PLATE WITH DEE-RINGS AND 20 TON PINTLE HITCH
- FLEET ENG. POLY FENDERS WITH STAINLESS STEEL BRACKETS
- HENDERSON FULL REAR MUD FLAPS
- RED & WHITE REFLECTIVE TAPE BOTH SIDES AND TAILGATE
- CHASSIS AND UNDERSIDE OF BODY WILL BE UNDERCOATED





Vendors & Contracts

By Category

All Vendors



Clear All

Kenworth

Class 6, 7 & 8 Vehicles & Chassis

#081716-KTC

Construction Equipment Fleet & Related

National Auto Fleet Group - Class 6, 7 & 8 Chassis

Class 6, 7 & 8 Chassis





RUSSELL TOWNSHIP/NJPA 8501 Kinsman Rd Novelty, OH 44072-9640 ID# 42393

Is this your organization?

Great news—your organization is already a Sourcewell member! Using the ID number provided on this page, you can immediately utilize Sourcewell awarded contracts by providing this number to the vendor you wish to purchase from.

Update your organization's information

Add a contact for your organization

Need help?

Contact our dedicated Membership Team at membership@sourcewell-mn.gov or 877-585-9706.





Sourcewell for Vendors >

Techs & Condition

Siteman

Privacy Policy

Acresologity